



UNI75

The UNI75 is a surface-mounted speaker from the Universals-series, but it distinguishes itself by its phenomenal capacity.

The slender multiplex casing has a polyurethane-coating, a "jacket" that makes it immune for any attack from outside. Both a double 5" driver and a horn tweeter were fitted. It will push out any detail, without distortion. It can easily handle 380 Watts of power. The dB-pressure ensures a tremendous range. Combine it with the AS1000 subwoofer to create a top notch interplay.

- ① The bracket will ensure perfect alignment, vertically as well as horizontally.
- ② Thanks to the professional Speakon connector, you can easily interconnect multiple units.



① u-bracket



② Speakon connector

TECHNICAL SPECIFICATIONS

range	<200m ²
system	2-way
woofer	2 x 5" MF transducer
tweeter	1" horn tweeter
bass reflex	yes
magnetic shielded	yes
amp power	200-380W (recommended)
spread differential	60 x 60°
sensibility	122dB
impedance	8Ω
frequency range	65Hz-20KHz
connection	Speakon NL4 in/out
dimensions (h x w x d)	430 x 170 x 230mm
weight / piece	7,5kg
composition	15 mm multiplex box with polyurethane coating
colour	black
suspension	u-wall bracket (incl.)



The UNI75 can be used in any space where sound is really relevant. Any hall will become a major dance venue! Any auditorium will be an ultimate place to listen.

**MADE IN
EUROPE**